

# Safety Reel

FOR SAFE PERFORMANCE IN WORKPLACES

## The New Generation

Hose Reels from CEJN  
for Highest Safety and  
Performance!



- **Safety**
- **Performance**
- **Durability**

## CEJN extends the range with open steel reels

Let us introduce the new extended range of open safety reels from CEJN. With our new open range, we meet our customers' requirements for a multitude of applications which complements other products from our wide range.

As always with CEJN products, **safety** has been top priority which is reflected in features like the controlled rewind system resulting in a reel that retracts the hose at a safe and steady pace. You will experience excellent **performance** with a compact high-flow swivel and a large chassi and frame that accommodates longer length and larger dimensions of hoses. To ensure long lasting **durability** the heavy duty steel reel has a powder coated finish for wear and challenging conditions. Another example is the unique axle with dual support system for maximum stability.

The new CEJN open hose reel collection can be adapted to use with air and water. All of our safety reels are designed with CEJN's core company values: **safety, performance, quality, innovation** and protecting the **environment**.



# Reference List Part Numbers



## CEJN PUR hose reels

CEJN #	Media	Hose	Length	Drum Size	Connection
19 911 3141	Air	9,5x13,5mm	60 ft (18m)	19,5" (495mm)	BSPT 3/8"
19 911 3146	Air	9,5x13,5mm	60 ft (18m)	19,5" (495mm)	NPT 3/8"
19 911 3150	Air	13x18mm	50 ft (15m)	19,5" (495mm)	BSPT 1/2"
19 911 3155	Air	13x18mm	50 ft (15m)	19,5" (495mm)	NPT 1/2"
19 911 3152	Air	13x18mm	75 ft (23m)	24" (610mm)	BSPT 1/2"
19 911 3157	Air	13x18mm	75 ft (23m)	24" (610mm)	NPT 1/2"
19 911 3153	Air	13x18mm	100 ft (30m)	24" (610mm)	BSPT 1/2"
19 911 3158	Air	13x18mm	100 ft (30m)	24" (610mm)	NPT 1/2"
19 911 3162	Air	16x21mm	75 ft (23m)	24" (610mm)	BSPT 3/4"
19 911 3167	Air	16x21mm	75 ft (23m)	24" (610mm)	NPT 3/4"
19 911 3171	Air	19x24mm	50 ft (15m)	24" (610mm)	BSPT 3/4"
19 911 3176	Air	19x24mm	50 ft (15m)	24" (610mm)	NPT 3/4"
19 911 3241	Water	9,5x13,5mm	60 ft (18m)	19,5" (495mm)	BSPT 3/8"
19 911 3246	Water	9,5x13,5mm	60 ft (18m)	19,5" (495mm)	NPT 3/8"
19 911 3250	Water	13x1 mm	50 ft (15m)	19,5" (495mm)	BSPT 1/2"
19 911 3255	Water	13x18mm	50 ft (15m)	19,5" (495mm)	NPT 1/2"
19 911 3253	Water	13x18mm	100 ft (30m)	24" (610mm)	BSPT 1/2"
19 911 3258	Water	13x18mm	100 ft (30m)	24" (610mm)	NPT 1/2"
19 911 3271	Water	19x24mm	50 ft (15m)	24" (610mm)	BSPT 3/4"
19 911 3276	Water	19x24mm	50 ft (15m)	24" (610mm)	NPT 3/4"

## CEJN EPDM rubber hose reels

CEJN #	Media	Hose	Length	Drum Size	Connection
19 911 4152	Air/water	1/2"	75 ft (23m)	24" (610mm)	BSPT 1/2"
19 911 4157	Air/water	1/2"	75 ft (23m)	24" (610mm)	NPT 1/2"
19 911 4153	Air/water	1/2"	100 ft (30m)	24" (610mm)	BSPT 1/2"
19 911 4158	Air/water	1/2"	100 ft (30m)	24" (610mm)	NPT 1/2"
19 911 4171	Air/water	3/4"	50 ft (15m)	24" (610mm)	BSPT 3/4"
19 911 4176	Air/water	3/4"	50 ft (15m)	24" (610mm)	NPT 3/4"

## CEJN hoseless reels

CEJN #	Media	Hose	Length	Drum Size	Connection
19 911 6141	Air/water	-	60 ft (18m)	19,5" (495mm)	BSPT 3/8"
19 911 6146	Air/water	-	60 ft (18m)	19,5" (495mm)	NPT 3/8"
19 911 6150	Air/water	-	25 ft ( 7m)	24" (610mm)	BSPT 1/2"
19 911 6155	Air/water	-	25 ft ( 7m)	24" (610mm)	NPT 1/2"
19 911 6151	Air/water	-	50 ft (15m)	24" (610mm)	BSPT 1/2"
19 911 6156	Air/water	-	50 ft (15m)	24" (610mm)	NPT 1/2"
19 911 6152	Air/water	-	75 ft (23m)	24" (610mm)	BSPT 1/2"
19 911 6157	Air/water	-	75 ft (23m)	24" (610mm)	NPT 1/2"
19 911 6153	Air/water	-	100 ft (30m)	24" (610mm)	BSPT 1/2"
19 911 6158	Air/water	-	100 ft (30m)	24" (610mm)	NPT 1/2"
19 911 6170	Air/water	-	25 ft (7m)	24" (610mm)	BSPT 3/4"
19 911 6175	Air/water	-	25 ft (7m)	24" (610mm)	NPT 3/4"
19 911 6171	Air/water	-	50 ft (15m)	24" (610mm)	BSPT 3/4"
19 911 6176	Air/water	-	50 ft (15m)	24" (610mm)	NPT 3/4"

Check with an authorized CEJN distributor for availability and prices. Other connections and sealing material on request. Some part numbers may be subject to minimum order quantities. CEJN reserves the right to make changes without further notification. Thread connections are listed according to ISO Standards